

OT60F3



General Information

Extended Product Type:	OT60F3
Product ID:	1SCA105076R1001
EAN:	6417019392066
Catalog Description:	OT60F3 Switch-disconnector
Long Description:	Front operated switch-disconnector. Types OT 16...125 include protected terminal clamps, IP 20.

Categories

Products » Low Voltage Products and Systems » Switches » Disconnect Switches

Ordering

EAN:	6417019392066
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	70 mm
Product Net Height:	74 mm
Product Net Depth:	100 mm
Product Net Weight:	0.36 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	81 mm
Package Level 1 Height:	86 mm
Package Level 1 Length:	112 mm
Package Level 1 Gross Weight:	0.36 kg
Package Level 1 EAN:	6417019392066

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q3
--------------	---

Technical UL/CSA

Ampere Rating UL/CSA:	60 A
Horse Power Rating UL/CSA:	acc. to UL 200V 20 Hp acc. to UL 208V 20 Hp acc. to UL 240V 20 Hp acc. to UL 480V 40 Hp acc. to UL 600V 40 Hp

Additional Information

Cable Cross-Section:	2.5...25 mm ²
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	3
Operating Mechanism:	Mechanism on top of the switch
Order Multiple:	1 piece
Pollution Degree:	3
Position of Line Terminals:	Top in - bottom out
Power Loss:	Per Pole 0.36 W
Product Main Type:	OT125E_125F
Product Name:	Switch-disconnector
Rated Operational Current AC-21A (I _e):	(380 ... 415V) 63 A (690V) 63 A (500V) 63 A
Rated Operational Current AC-22A (I _e):	(380 ... 415 V) 63 A (500 V) 63 A (690 V) 63 A
Rated Operational Current AC-23A (I _e):	(380 ... 415 V) 45 A (690 V) 40 A (500 V) 63 A
Rated Short-time Withstand Current (I _{cw}):	for 1.0s 2.5 kiloampere rms

Certificates and Declarations (Document Number)

Declaration of Conformity - CE: [1SCC301010D0201](#);

Classifications

ETIM 5.0: EC000216 - Switch disconnecter

Object Classification Code: Q

