

## OT63F3



### General Information

Extended Product Type:	OT63F3
Product ID:	1SCA105332R1001
EAN:	6417019392912
Catalog Description:	OT63F3 Switch-disconnector
Long Description:	Front operated switch-disconnector. Types OT 16...125 include protected terminal clamps, IP 20.

### Categories

Products » Low Voltage Products and Systems » Switches » Disconnect Switches

### Ordering

EAN:	6417019392912
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

### Dimensions

Product Net Width:	53 mm
Product Net Height:	92 mm
Product Net Depth:	73 mm
Product Net Weight:	0.27 kg

### Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	63 mm
Package Level 1 Height:	85 mm
Package Level 1 Length:	103 mm
Package Level 1 Gross Weight:	0.27 kg
Package Level 1 EAN:	6417019392912

### Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q3
--------------	---

### Technical UL/CSA

Ampere Rating UL/CSA:	60 A
Horse Power Rating UL/CSA:	acc. to UL 200V 15 Hp acc. to UL 208V 15 Hp acc. to UL 240V 15 Hp acc. to UL 480V 30 Hp acc. to UL 600V 30 Hp

### Additional Information

Cable Cross-Section:	1.5...35 mm <sup>2</sup>
Conventional Free-air Thermal Current (I <sub>th</sub> ):	q=40°C 63 A
Conventional Thermal Current (I <sub>the</sub> ):	Fully Enclosed 63 A
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	3
Operating Mechanism:	Mechanism on top of the switch
Pollution Degree:	3
Position of Line Terminals:	Top in - bottom out
Power Loss:	Per Pole 2.8 W
Product Main Type:	OT63E_63F
Product Name:	Switch-disconnector
Rated Impulse Withstand Voltage (U <sub>imp</sub> ):	8 kV
Rated Insulation Voltage (U <sub>i</sub> ):	750 V
Rated Operational Current AC-21A (I <sub>e</sub> ):	(690V) 63 A (500V) 63 A (380 ... 415V) 63 A
Rated Operational Current AC-22A (I <sub>e</sub> ):	(380 ... 415 V) 63 A (500 V) 63 A (690 V) 63 A
Rated Operational Current AC-23A (I <sub>e</sub> ):	(690 V) 20 A (380 ... 415 V) 45 A (500 V) 45 A

**Rated Operational Power AC-23A (P<sub>e</sub>):** (220 ... 240V) 11 kW  
(400V) 22 kW  
(415V) 22 kW  
(500V) 22 kW  
(690V) 11 kW

**Rated Operational Voltage (U<sub>e</sub>):** 750 V

**Rated Short-time Withstand Current (I<sub>cw</sub>):** for 1.0s 1 kiloampere rms

---

### Certificates and Declarations (Document Number)

---

**Declaration of Conformity - CE:** [1SCC301167D0201](#);

---

### Classifications

---

**E-nummer:** 3170940

**ETIM 5.0:** EC000216 - Switch disconnecter

**Object Classification Code:** Q

---

