

OT80F3



General Information

Extended Product Type:	OT80F3
Product ID:	1SCA105798R1001
EAN:	6417019397016
Catalog Description:	OT80F3 Switch-disconnector
Long Description:	Front operated switch-disconnector. Types OT 16...125 include protected terminal clamps, IP 20.

Categories

Products » Low Voltage Products and Systems » Switches » Disconnect Switches

Ordering

EAN:	6417019397016
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	53 mm
Product Net Height:	92 mm
Product Net Depth:	73 mm
Product Net Weight:	0.27 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	84 mm
Package Level 1 Height:	64 mm
Package Level 1 Length:	103 mm
Package Level 1 Gross Weight:	0.27 kg
Package Level 1 EAN:	6417019397016

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q3
--------------	---

Technical UL/CSA

Ampere Rating UL/CSA:	60 A
Horse Power Rating UL/CSA:	acc. to UL 200V 20 Hp acc. to UL 208V 20 Hp acc. to UL 240V 20 Hp acc. to UL 480V 40 Hp acc. to UL 600V 40 Hp

Additional Information

Cable Cross-Section:	1.5...35 mm ²
Conventional Free-air Thermal Current (I _{th}):	q=40°C 80 A
Conventional Thermal Current (I _{the}):	Fully Enclosed 80 A
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	3
Operating Mechanism:	Mechanism on top of the switch
Pollution Degree:	3
Position of Line Terminals:	Top in - bottom out
Power Loss:	Per Pole 2.8 W
Product Main Type:	OT80F
Product Name:	Switch-disconnector
Rated Impulse Withstand Voltage (U _{imp}):	8 kV
Rated Insulation Voltage (U _i):	750 V
Rated Operational Current AC-21A (I _e):	(500V) 80 A (690V) 80 A (380 ... 415V) 80 A
Rated Operational Current AC-22A (I _e):	(380 ... 415 V) 80 A
Rated Operational Current AC-23A (I _e):	(380 ... 415 V) 75 A (500 V) 58 A (690 V) 20 A
Rated Operational Power AC-23A	(220 ... 240V) 22 kW

(P_e): (400V) 37 kW
(415V) 37 kW
(500V) 37 kW
(690V) 18.5 kW

Rated Operational Voltage (U_e): 750 V

Rated Short-time Withstand Current (I_{cw}): for 1.0s 1 kiloampere rms

Certificates and Declarations (Document Number)

Declaration of Conformity - CE: [1SCC301167D0201](#);

Classifications

E-nummer: 3170941

ETIM 5.0: EC000216 - Switch disconnecter

Object Classification Code: Q

