

## D-SUB bus connector - SUBCON 15 HD/F-SH - 5604603

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



D-SUB connector, 15-pos. female connector, one cable entry < 35°, universal type for all systems, pin assignment: 1, 2, 3, ..., 14, 15 to screw connection terminal block

### Product Features



### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	77.8 GRM
Custom tariff number	85366990
Country of origin	United States

### Technical data

#### Dimensions

Max. cable diameter	12.7 mm
Min. cable diameter	4 mm
Width	16 mm
Height	49.8 mm
Length	61 mm

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 75 °C
---------------------------------	------------------

#### General

Nominal voltage $U_N$	48 V AC/DC
Nominal current $I_N$	1 A
Signal	Point-to-point
Insertion/withdrawal cycles	> 50
SUBCON fixing screws	4-40 UNC
Tightening torque	0.4 Nm
Housing material	ABS, metal-plated

## D-SUB bus connector - SUBCON 15 HD/F-SH - 5604603

### Technical data

#### General

Pin assignment	All connections are 1:1 on the screw terminal block
----------------	---

#### Connection data

Connection	D-SUB connection
Number of positions	15
Connection method	D-SUB connector

### Classifications

#### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209

#### ETIM

ETIM 3.0	EC001132
ETIM 4.0	EC001132
ETIM 5.0	EC001132

#### UNSPSC

UNSPSC 6.01	30211802
UNSPSC 7.0901	39121402
UNSPSC 11	39121402
UNSPSC 12.01	39121402
UNSPSC 13.2	39121402